### **PCT**

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



- INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) (51) International Patent Classification 6: (11) International Publication Number: WO 98/49423 E21B 43/10, 43/08 (43) International Publication Date: 5 November 1998 (05.11.98)
- (21) International Application Number:

(22) International Filing Date:

27 April 1998 (27.04.98)

(30) Priority Data:

97201267.8 28 April 1997 (28.04.97) (34) Countries for which the regional or international application was filed:

- (71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPU B.V. [NL/NL]; Carel van Bylandtiaan 30, NL-2596 HR The Hague (NL).
- (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 4th Avenue S.W., Calgary, Alberta T2P
- (72) Inventor: DONNELLY, Martin; Badhuisweg 3, NL-1031 CM Amsterdam (NL).


PCT/EP98/02577

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PI, PT, RO, RU, SD, SE, SG, SI, SK, SI, TI, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, II, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BI, CF, CG, CI, CM, GA, QN, ML, MR, NE, SN, TD, TG).

### Published

With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Tille: EXPANDABLE WELL SCREEN



#### (57) Abstract

An expandable well screen for preventing migration of sand or other solid particles into a hydrocarbon fluid production well comprises An expansione wen screen or prevening migration of sand or other sold particles into a hydrocarbon had production wen comprises a number of filter sheets (3) with circumferential slots (6), which sheets (3) are secured in an iris-shaped configuration and co-axial to an expandable slotted carrier tube (1) such that as result of expansion of the tube (1) the amount of overlap between adjacent filter sheets (3) is reduced. The circumferential slot pattern of the slots (6) enables the filter sheets (3) to slide easily relative to each other and to avoid buckling and/or tearing of the filler sheets during the expansion process.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphiets publishing international applications under the PCT.

AL	Albania		P1-				
AM	Annenia	ES	Spain	LS	Lexicho	St	Slovenia
AT		PI	Fished	LT	Litheanie	SK	Slovalda
	Austria	FR	Prance	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Letvia	SZ	Swaziland
AZ	Azorbaijan	GB	United Kingdom	MC	Monaco	110	Chad
BA	Bosnia and Herzegovina	CR	Georgia	MD	Republic of Moldova	TC	Togo
Bø	Barbados	CH	Ghana	MG	Madagascar	TJ	Tajikistan
BB	Belgium	C(X)	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Paso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobas
BJ	Bezin	IE	keland	MN	Mongolia	ÜA	Utraine
BR	Brazil	IL.	faraci	MR	Mauritania	UG	Uganda
BY	Betarus	13	feeland	MW	Malawi	US	United States of A
CA	Cenada	IT	kely	MX	Mexico	UZ.	
CF	Central African Republic		Japan	NE	Niger	VN	Urbekistan Viet Nam
œ	Congo	KE	Kenya	NL	Netherlands	YU	
CH	Switzerland	KC	Kyrgyzstan	NO	Norway		Yogoslavia
а	Côte d'Ivoire	KP	Democratic People's	NZ	New Zeabod	27 <del>.Y</del>	Zimbab 200
CM	Caracroco		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT			
CU	Cuba	KZ,	Kazakuten	RO	Portegal Romania		
CZ	Ctoch Republic	ic	Saint Lucia	RU			
DE	Germany	ũ	Liechtenstein	_	Residen Pederation		
DK	Denmark	LK	Sri Lanka	SD	Suden		
BE.	Estonia	LR		SB	Sweden		
46	CHURIA	LK	Liberia	SC	Singapore		

#### EXPANDABLE WELL SCREEN

The invention relates to an expandable well screen for preventing migration of solid particles into a hydrocarbon fluid production well.

More particularly, the invention relates to an expandable well screen which comprises a number of filter sheets which are secured in an iris-shaped configuration and co-axial to an expandable slotted carrier tube such that as a result of expansion of the tube the amount of overlap between adjacent filter sheets is reduced.

Such an expandable well screen is disclosed in applicant's co-pending international patent application PCT/EP96/04887.

Figure 3 of this prior art reference discloses that the filter sheets consist of plates in which a series of circular perforations are present. The size of these perforations is chosen such that solid particles larger than the size of the hole are prevented from flowing into the well.

A suitable expandable slotted carrier tube for use with the screen is disclosed in international patent application PCT/EP93/01460.

It has been found that filter sheets which are secured to an expandable slotted carrier tube are deformed considerably during the process of expanding the carrier tube by moving an expansion mandrel therethrough. The carrier tube normally shortens during the expansion process as a result of opening of the axial slots towards a diamond shape.

This may cause the filter sheets to buckle to accommodate the carrier tube shortening and friction

· 10

5

20

15

25

10

15

20

25

30

between the overlapping filter sheets and the carrier tube or tubes may cause the filter sheets to tear.

An object of the present invention is to provide a well screen comprising an iris-shaped configuration of filter sheets which do not buckle and which slide easily relative to each other and relative to the carrier tube during the process of expanding the carrier tube.

The well screen according to the invention thereto comprises filter sheets having slots which are oriented in a substantially circumferential orientation with respect to the carrier tube.

When used in this specification the reference to a circumferential arrangement of slots means that the slots each are directed in a substantially tangential orientation with respect to the carrier tube and such the slots are oriented substantially transversal to the central axis and any axial slots of the carrier tube.

Preferably the filter sheets consist of elongate strips with staggered rows of slots in a transversal direction with respect to a longitudinal axis of each strip.

The pattern of slots is preferably such that alternate rows are displaced up to half a slot pitch in the transverse direction, the length of the slots is greater than half the transverse slot pitch, and the pattern of slots is continued through the longitudinal edges of the strips.

It is also preferred that each strip is secured at regularly spaced points along its length to the expandable slotted carrier tube and that each strip is secured to the expandable slotted carrier tube at said points by either spot welding, brazing, soldering, gluing, riveting or screwing the strip to the tube at each of said points.

10

20

25

30

35

These and further aspects, features and advantages of the well screen according to the present invention will become apparent from the accompanying claims, abstract and the following detailed description with reference to the drawings.

In the drawings:

Fig. 1 is a cross-sectional view of a well-screen comprising an iris-shaped configuration of filter sheets according to the invention;

Fig. 2 is a longitudinal sectional view of the well screen of Fig. 1;

Fig. 3 is a side view of the well screen of Fig. 1 and 2 in which the protective surrounding tube has been omitted; and

Fig. 4 and Fig. 4A, B, C and D show the original shape and deformation of the circumferential clots near a longitudinal edge of the filter sheets before, during and after the expansion process.

Referring now to Fig. 1 there is shown an expandable slotted carrier tube 1 which is surrounded by a well screen 2 which comprises a series of filter sheets 3 which are arranged in an iris-shaped configuration around the carrier tube 1. As shown in Fig. 2 and 3 the filter sheets 3 consist of elongate rectangular strips which are each, as shown in Fig. 1 secured to the carrier tube 1 at attachment points 4 located on or close to the longitudinal centreline of the filter sheet 3 by for example spot welding, brazing, soldering, gluing, riveting or screwing at regularly spaced points along the length of the carrier tube 1. The attachment points are located on the nodes between the ends of the slots of the carrier tube 1.

The filter sheets 3 overlap each other in both axial and circumferential direction such that during and after the expansion process which is illustrated in Fig. 4 at

10

15

20

25

30

35

least some overlap remains between adjacent filter sheets 3.

In Fig. 3 the protective surrounding tube 5 which is shown in Figs. 1 and 2 has been omitted to show that the filter sheets 3 each comprise a series of staggered rows of circumferential slots 6 which are oriented in a substantially tangential direction with respect to the carrier tube 1 and substantially transversal to the axial slots 7 of the carrier tube 1 and to the central axis 8 of the carrier tube 1.

As shown in Fig. 4 the carrier tube 1 is expanded by an expansion cone 9 during the expansion process such that the axial slots 7 deform into a diamond shape.

The expansion causes the carrier tube 1 to shorten and as illustrated in Figs. 4A-D the circumferential slots 6 at and near the longitudinal edges of the filter sheets 3 will initially open up to the diamond shape shown in Fig. 4B, then close to the X-shape shown in Fig. 4C and then partly re-open again to the key-hole shape shown in Fig. 4D.

The illustrated sequential opening and closing of the circumferential slots 6 provides axial flexibility to the filter sheets 3 which prevents buckling or tearing of the fragile sheets 3 during expansion of the carrier tube 1.

The circumferential slots 6 also allow the overlapping sheets 3 to slide easily relative to each other during the expansion process.

It is observed that instead of arranging the filter sheets 3 in a longitudinal direction around the carrier tube 1 as illustrated in Fig. 3, the filter sheets 3 may also be arranged in a shallow helix around the carrier tube 1. In such case the helix angle should be selected small enough so that the deviation of the slots 6 from the tangential direction of the carrier tube 1 is less than 20 degrees.

10

15


20


#### CLAIMS


- 1. An expandable well screen for preventing migration of solid particles into a hydrocarbon fluid production well, which screen comprises a number of filter sheets which are secured in an iris-shaped configuration and co-axial to an expandable slotted carrier tube such that as a result of expansion of the tube the amount of overlap between adjacent filter sheets is reduced, wherein the filter sheets comprise slots which are oriented in a substantially circumferential orientation with respect to the carrier tube.
- 2. The well screen of claim 1, wherein the filter sheets consist of elongate strips with staggered rows of slots in a transversal direction with respect to a longitudinal axis of each strip.
- 3. The well screen of claim 2, wherein the pattern of slots is such that alternate rows are displaced up to half a slot pitch in the transverse direction, the length of the slots is greater than half the transverse slot pitch, and the pattern of slots is continued through the longitudinal edges of the strips.
- 4. The well screen of claim 3, wherein each strip is secured at regularly spaced attachment points along its length to the expandable slotted carrier tube.
- 5. The well screen of claim 4, wherein each strip is secured to the expandable slotted carrier tube at said attachment points by either spot welding, brazing, soldering, gluing, riveting or screwing the strip to the tube at each of said points.
- 30 6. The well screen of claim 5, wherein the regularly spaced attachment points are located on the nodes between


the ends of the slots of the expandable slotted carrier  $\stackrel{\text{\tiny --}}{}$  tube.

7. The well screen of claim 6, wherein the longitudinal axis of each strip is substantially parallel to a central axis of the carrier tube both before and after expansion of the carrier tube.









## INTERNATIONAL SEARCH REPORT

Inter, and Application No PCT/EP 98/02577

IPC 6	E21843/10 E21843/08	
According to	o international Patent Classification(IPC) or to both national classification and IPC	
	SEARCHED	
Minimum do IPC- 6	cumertation searched (classification system followed by classification symbols) E 21B	
Documentat	tion searched other than minimum documentation to the extent that such documents are included in the field	M Mearched
Electronic d	ata base consulted during the international aearch (name of data base and, where practical, search terms o	sadi
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT	
Calegory ·	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,P	WO 97 17524 A (SHELL CANADA LTD :SHELL INT RESEARCH (NL)) 15 May 1997 cited in the application see the whole document	1
A .	US 3 353 599 A (V.N. SWIFT) 21 November 1967 see column 4, line 70 - column 5, line 10 see figure 5	1
A	US 2 812 025 A (J.U. TEAGUE ET AL) 5 November 1957 see the whole document	1
Furti	her documents are listed in the continuation of box C.    X   Patent family members are by	Ited in annex,
"A" docume consid "E" earlier of filing of "L" docume which criatio "O" docume other of "P" docume later di	regories of cited documents:  In I later document published after the or periority data and not in conflict cased to be of perticular relevance becomes but published on or after the intermational tase.  In which may throw doubts on priority claims or in cloth or sold or conflict cannot be considered novel or or in cloth or sold or s	with the application but or theory underlying the the claimed invention arror to considered to the document is taken alone the claimed invention an inventive step when the or more other such docu- tivious to a person skilled along family
	0 August 1998 28/08/1998	
Name and r	making address of the ISA Authorized officer  European Patent Office, P.8. 5816 Patentlaan 2 NL -2290 NY Pijawik  Tel. (-31-70) 340-2040, Tx. 31 651 epo.nl.  Fax: (-31-70) 340-3016  Schouten, A	

## INTERNATIONAL SEARCH REPORT

information on patent family members

Inter. nel Application No PCT/EP 98/02577

Patent document cited in search repor	1	Publication date	Patent landy member(s)	Publication date
WO 9717524	Α	15-05-1997	AU 7568096 A	29-05-1997
US 3353599	Α	21-11-1967	NONE	
US 2812025	Α	05-11-1957	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

## IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.